

GSW-2401

24-port 10/100/1000Mbps Gigabit Ethernet Switch



The PLANET GSW-2401 is 10/100/1000Mbps Gigabit Ethernet switch with 24 ports respectively, and non-blocking wire-speed performance. With a 48Gbps internal switching fabric. The GSW-2401 can handle extremely large amounts of data in a secure topology linking to a backbone or high capacity servers. The GSW-2401 has 8K MAC Address table and provides 400KB buffer memory. The GSW-2401 offers wire-speed packets transfer performance without risk of packet loss. The high data throughput of GSW-2401 make it ideal for most Gigabit environments, especially network upgrades to a Gigabit environment.

All RJ-45 copper interfaces support 10/100/1000Mbps Auto-Negotiation for optimal speed detection through RJ-45 Category 6, 5 or 5e cables. Support is standard for Auto-MDI/MDI-X that can detect the type of connection to any Ethernet device without requiring special straight or crossover cables.

The Flow Control function allows your Gigabit switch supported routers and servers to directly connect to this switch for fast, reliable data transfer.

▶▶ KEY FEATURE

- Complies with IEEE802.3, 10Base-T, IEEE802.3u 100Base-TX, IEEE802.3ab 1000Base-T
- 24-port 10/100/1000 Mbps Gigabit Ethernet ports
- Features Store-and-Forward mode with wire-speed filtering and forwarding rates
- Hardware based 10/100Mbps, half/full duplex and 1000Mbps full duplex mode, flow control and auto-negotiation
- IEEE802.3x flow control for full duplex operation and Backpressure for half duplex operation
- Integrated address look-up engine, support 8K absolute MAC addresses
- Provide 400KB buffer memory
- 9K Jumbo packet support
- Automatic address learning and address aging
- Supports Auto MDI/MDI-X function
- Support CSMA/CD protocol
- 100~240VAC, 50~60Hz universal Power input
- FCC, CE class A compliant

▶▶ SPECIFICATION

Product	24-port 10/100/1000Mbps Gigabit Ethernet Switch (24 RJ-45)
Model	GSW-2401
Hardware Specification	
10/100/1000Base-T Ports	24
Switch Processing Scheme	Store-and-Forward
Switch fabric	48Gbps
Throughput (packet per second)	35.7Mpps
Address Table	8K entries
Share data Buffer	400KB
Jumbo packet size	9K
Flow Control	Back pressure for half duplex, IEEE 802.3x Pause Frame for full duplex
Dimensions	440 x 200 x 44 mm (1U height)
Weight	2.8 kg
Power Requirement	100~240 VAC, 3.0A, 50-60 Hz
Temperature	Operating: 0~50 degree C, Storage -40~70 degree
Humidity Operating	10% to 90%, Storage: 5% to 95% (Non-condensing)
Standards Conformance	
Regulation Compliance	FCC Part 15 Class A, CE
Standards Compliance	IEEE 802.3 (Ethernet) IEEE 802.3u (Fast Ethernet) IEEE 802.3ab(Gigabit Ethernet) IEEE 802.3x (Full-duplex flow control)

▶▶ APPLICATION

- Backbone Switch**
With up to 48 Gigabits per second of non-blocking switch fabric, the GSW-2401 can easily provide the high bandwidth required both now and in the future.
- Server Farm Switch**
Providing either 24 Gigabit Ethernet ports, the GSW-2401 is ideal for use as a server farm switch connecting your servers and powerful desktops.

▶▶ ORDERING INFORMATION

- ▶ **GSW-2401** 24-port 10/100/1000Mbps Gigabit Ethernet Switch (24 RJ-45)



PLANET Technology Corp.

11F, No. 96, Min Chuan Road, Hsin Tien, Taipei, Taiwan, R.O.C.
TEL:886-2-2219-9518 FAX:886-2-2219-9528

E-mail: sales@planet.com.tw <http://www.planet.com.tw>

VoIP Gateway : vip.planet.com.tw

Planet reserves the right to change specification without prior notice.
All brand names and trademarks are property of their respective owners.
Copyright 2004 © PLANET Technology Corp. All right reserved

